

LCD 17" Professional CCTV Monitor

Display	Screen Size	17 Inch
	Max. Resolution	1280 x 1024 @ 60Hz
	Pixel Pitch	0.264mm x 0.264mm
	Brightness	300cd/m2
	Contrast Ratio	1000 : 1
	Aspect Ratio	5:4
	Viewing Angle (H/V)	160° / 160°
	Display Colour	16.2 Million
	Response Time	<5ms
	Video System	NTSC / PAL
Audio	Frequency (H)	31 ~ 64 KHz(H)
	Frequency (V)	55 ~ 75 KHz(V)
Audio	Built-in Speakers	Yes (2W x 2)
	Gradual Volume Increase	Yes
Interface	Video In / Out (BNC type)	2/2
	S-Video In / Out	1/1
	RGB In (15Pin D-sub)	1
	DVI / HDMI	1/1
	Audio In / Out (RCA type)	2/1
Transmitter	PC Stereo Input	1
	Remote Controller	Yes
Special features	PIP (Picture In Picture)	PIP/VOV/PBP
	Filter type	3D Comb Filter / De-Interlace
	LCD Protection Glass	Yes
	Rack Mountable Kit	Optional
	Multi-lingual Language	English, Spanish, French, German, Italian, Portuguese, Dutch
Dimension	VESATM DDC Compatible	Yes
	Outline Dimension	389.7 x 350.1 x 78mm
	Net Weight	6.2KG
Cabinet	Gross Weight	7.8KG
	Finish / Tilt Stand	Black / Yes
Mounts	VESA Mounts size	100 x 100mm (BS M4 x 10mm Screw)
Warranty	Parts / Labour	2 Year - New for OLD
	MTBF (Approx.)	50,000 hours
Regulations	TUV-NRTL (Same as UL), CB, FCC(B), CE-Emc(LVD)	
Power consumption	< On / < Stand-by	<40W
Power type	Electrical Ratings	AC100 ~ 240V (50/60Hz) DC 12V / 4.12A Adapter

17RTC



Features

LCD Protection Glass
Multiple Connections:
BNC 2x In / Out
S-Video In / Out
3D Comb Filter / De-Interlace
Built-In Speakers
5ms response, 1000:1 Contrast
Built for 24x7x365 Operation



Hantarex International Limited
34 Salisbury Street
Marylebone
London NW8 8QE

Phone: +44(0)20 8778 1414
Fax: +44(0)20 8659 9348
E-Mail: sales@hantarex.com