

LCD 19" Professional CCTV Monitor

Display	Screen Size	19"
	Resolution	1280 X 1024@60Hz
	Contrast Ratio	1,000:1
	Brightness	300cd/m2
	Aspect Ratio	5/4 (4:3)
	Colour Depth	16.7M
	Viewing Angle(H/V)	160°/160°
	Pixel Pitch	0.294 x 0.294 mm
	Response Time	< 5ms
	Scanning Frequency (Horizontal)	31 ~ 64KHz
	Scanning Frequency (Vertical)	55 ~ 75Hz
	Video System	NTSC / PAL
Audio	Built-in Speakers	Yes (2W x 2)
	Gradual Volume Increase	Yes
Interface	Video In / Out (BNC type)	2/2
	S-Video In / Out	1/1
	RGB In (15Pin D-sub)	1
	DVI / HDMI	01-Jan
	Audio In / Out (RCA type)	2
	PC Stereo Input	1
Transmitter	Remote Controller	Yes
Special features	PIP (Picture In Picture)	PIP / VOV / PBP
	Filter type	3D Comb filter / De-Interlace
	LCD Protection Glass	Yes
	Rack Mountable Kit	Optional
	Multi-lingual Language	English, Spanish, French, German, Italian
	Camera Mounting Hole	2(Upper/Bottom)
	VESATM DDC Compatible	Yes
Dimension	Outline Dimension (With Stand)	428.5 x 380.2 x 83 mm
	Packaging dimension	540 x 485 x 180 mm
	Net Weight	7.5 Kg (16.5 lbs)
	Gross Weight	9 Kg (19.8 lbs)
Cabinet	Finish / Tilt Stand	Black / Yes
Mounts	VESA Mounts size	100 x 100mm (BS M4 x 10mm Screw)
Warranty	Parts / Labour	2 Year - New for OLD
	MTBF (Approx.)	50,000 hours
Regulations	TUV-NRTL (Same as UL), CB, FCC(B), CE-Emc(LVD)	
Power consumption	< On / < Stand-by	<45 W / Power Saving (EPA,VESA DPMS, Nutek Compliant)
	Electrical Ratings	AC100~240V (50/60Hz) DC 12V / 4.12A
Power type		
Environment	Operating Temperature	10~40°C / 50~104°F

19RTC



Features

LCD Hard Glass Protection
 Metal Cabinet
 Multiple Connection:
 BNC 2 x In / Out
 S-Video In / Out
 DVI / HDMI
 VGA
 3D Comb Filter / Deinterlace
 Built-In Speakers
 5ms response, 1000:1 Contrast
 Built for 24x7x365 Operation



Hantarex International Ltd
 Unit 14 - Forest Hill Business Centre
 Forest Hill
 London SE23 3JF

Phone: +44(0)20 8778 1414
 Fax: +44(0)20 8659 9348
 E-Mail: sales@hantarex.com